



SOLID EZCLEAN

Low Odour Premium Quality Velvet Sheen Wall Coating
That Is Highly Washable And Stain Resistant.



DESCRIPTION

SOLID EZCLEAN is a low odour premium quality velvet sheen wall coating that is highly washable and stain resistant.

BENEFITS

- > Hero Ingredient: unique stain barrier that forms a multi-layered protective coating preventing dirt from penetrating the paint.
- > Breathe easy, virtually no odour.
- > Dries to a hard, velvet sheen that will withstand repeated washing.
- > A luxury wall coating and a hard wearing finish.
- > Quick drying - 2 coats can be applied in one day.
- > Stain resistant and easily cleaned.
- > No added lead.

USES

SOLID EZCLEAN is for new and old interior cement plaster walls, fibre-board, ceiling board, gypsum plaster, metal and wood. Ideal for bedrooms, passages, offices and public buildings where a hard wearing luxurious velvet sheen finish is required.

PACKING & COVERAGE

SOLID EZCLEAN have coverage of 10 ~ 12 m² / liter on single coat (approx. 40 µm). The coverage of **SOLID EZCLEAN** depends on the surface.

SHELF LIFE & STORAGE

SOLID EZCLEAN will have a shelf life of 12 months in unopened container when kept in dry conditions at a temperature between 5 ~ 45 °C. Storage at higher temperature or high humidity may reduce shelf life.



HOW TO USE

Ensure that surfaces are dry, firm, and free from dust, dirt, grease and oil before painting.

Surface Preparation : Surface must be dry. **SOLID EZCLEAN** may be applied directly to render or plaster surfaces, cement plaster, concrete, gypsum surfaces, unglazed brickwork, fibre-cement, ceiling boards. On plasterboard and over filling it is advisable to apply one coat of **SOLID ECO PRIME**, to reduce the difference in porosity of the joints. On old synthetic paint apply **SOLID ECO PRIME** after industry standard preparation.

Application Method: Apply 2 or more coats to correctly prepared surfaces so as to achieve complete obliteration. For airless spraying thinning is not required



HEALTH & SAFETY

Avoid contact with eyes and skin. Wear suitable protective clothing. Avoid painting during inclement weather or if temperature is below 10 °C. Do not wash for 7 days after painting. To ensure that colours on a project are consistent check that batch numbers and product codes are the same.

PRODUCT RESTRICTION :

- > Avoid painting during inclement weather or if temperature is below 10 °C.
- > Do not wash for 7 days after painting.
- > To ensure that colours on a project are consistent check that batch numbers and product codes are the same.

Disclaimer : The information provided in the data sheets is based on both current development of work and years of field experience. Efforts are made to ensure that the information is reliable, however, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of continuing research and development (R&D) undertaken in our laboratories, we advise customers to ensure that the data sheets provided are not superseded by an updated publication. All products are sold are subject to our standard condition of sale, which is available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local SOLID representative.



FACTORY OFFICE

Lot 772 (10-14), Jalan Subang 4, Kawasan Perindustrian Sg. Penaga 47620 Subang Jaya, Selangor Darul Ehsan, MALAYSIA.

+603-8081 4777 / 4776

info@solidsolutions.com.my

+603-8081 4771

www.solidsolutions.com.my