



SOLID VARNISH

Wood Varnish For Internal And External Use



BENEFITS

- > Long lasting performance.
- > Easy to apply.
- > Quick dry.

DESCRIPTION

SOLID VARNISH is a highly durable solvent-based varnish, which is used over bare wood and previously stained or varnished surfaces. It withstands knocks, scuffs and spills and is suitable for internal and external wood, veneer and chipboard. The product contains 40 percent solid content in order to provide a seamless and tough finish.

USES

- > Suitable for interior and external uses.
- > Veneer.
- > Wood frames.
- > Chipboard.

PACKING & COVERAGE

SOLID VARNISH comes in a standard packing of 5 & 20 litre pail. The product covers 15 m² per liter per coat (It may vary based on the substrate condition). The aforementioned coverage is based on 30microns Dry Film Thickness (DFT).

SHELF LIFE & STORAGE

SOLID VARNISH will have a shelf life of 12 months in unopened container when kept in dry conditions at a temperature between 5 ~ 45 °C. Storage at higher temperature or high humidity may reduce shelf life.

HEALTH & SAFETY

If skin or eye contact occurs, wash thoroughly with clean water and seek medical advice. Full health and safety details are given in product safety data sheet.



HOW TO USE

Surface Preparation : To achieve optimum results, ensure surfaces to be varnished are sound, clean and dry (new surfaces particularly must be fully dry) before treating. Remove all loose and defective coatings. Do not use linseed oil putty for making good with natural wood finishes. In multi-coat work, it is advisable to lightly rub down between coats, in the direction of the grain, using a suitable grade of sandpaper and then wipe off with a damp, lint free cloth.

Application : Stir the product thoroughly before using. The product is recommended to be applied using a brush only. It is not meant to be thinned with other solvents.

Cleaning : After use, remove as much product as possible from equipment before cleaning with degreaser.

SOLID VARNISH



QUALITY ASSURANCE

SOLID manufactures the entire range of construction chemical under compliance of SIRIM and other international standards (ASTM, BS, GBI, LEED).

TECHNICAL SERVICES

While new advance and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel and experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

Disclaimer : The information provided in the data sheets is based on both current development of work and years of field experience. Efforts are made to ensure that the information is reliable, however, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of continuing research and development (R&D) undertaken in our laboratories, we advise customers to ensure that the data sheets provided are not superseded by an updated publication. All products are sold are subject to our standard condition of sale, which is available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local SOLID representative.



FACTORY OFFICE

Lot 772 (10-14), Jalan Subang 4, Kawasan Perindustrian Sg. Penaga
47620 Subang Jaya, Selangor Darul Ehsan, MALAYSIA.

+603-8081 4777 / 4776

+603-8081 4771

info@solidsolutions.com.my www.solidsolutions.com.my