



SOLIDGLOSS PAINT

High Gloss Paint for Internal and External Use



DESCRIPTION

SOLIDGLOSS is an oil modified alkyd-based enamel paint, specially formulated for interior and exterior metal and wood surfaces giving them a touch of brilliance and breathing colourful life into your home. This high gloss paint will provide a lasting beauty even in harsh weather and helps to prevent fungus growth.

USES

For decoration and protection of both interior and exterior wood and metal surfaces.

PACKING & COVERAGE

SOLIDGLOSS comes in a Standard Packing of 5 and 20 liter metal pail. The product covers 0.4 liter / m² / 2 coats (It may vary based on the substrate condition). The aforementioned coverage is based on 35 microns Dry Film Thickness (DFT).



PHYSICAL PROPERTIES

Color	A wide range of colors (refer to SOLID color chart).
Appearance	Glossy.
Recommended no. of coats	1 ~ 2 coats.
Drying Time	2 hours (depending on temperature and site humidity), but cures within 6 hours (maximum).
Re-coating Estimated Time	8 hours (depending on humidity and temperature of substrate).

SHELF LIFE & STORAGE

SOLIDGLOSS will have a shelf life of 12 months in unopened container when kept in dry conditions at a temperature between 5 ~ 45 °C. Storage at higher temperature or high humidity may reduce shelf life.

HEALTH & SAFETY

If skin or eye contact occurs, wash thoroughly with clean water and seek medical advice. Full health and safety details are given in product safety data sheet.

HOW TO USE

New Surfaces:

Metal : Surface must be free from dirt, grease and other contaminants or laitance. Ferrous substrate should be sanded or wire-brushed to remove mild rust. Ensure that the surface is dry before application.

Wood : Wood must be dry and free from dirt, grease and other contaminants or laitance. Sandpapering is required to ensure that the surface is smooth for application. The surface needs to be dry for application.

Existing Surfaces : Any loose and flaking paint film must be scraped off on both wood and metal. Defective areas should be sanded and smoothened. For ferrous substrates, rust should be removed thoroughly. The entire surface must finally be dry and free from dirt, grease and other contaminants or laitance. The scraped areas should be primed prior to painting.

APPLICATION METHOD

Airless Spray Gun : The paint is ready for use after thorough stirring. Does not require thinning.

Brush or Roller : The paint is ready for use after thorough stirring. If necessary, thin with 5% of **SOLID THINNER**.

SOLIDGLOSS PAINT



QUALITY ASSURANCE

SOLID manufactures the entire range of construction chemical under compliance of SIRIM and other international standards (ASTM, BS, GBI, LEED).

TECHNICAL SERVICES

While new advance and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel and experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

Disclaimer : The information provided in the data sheets is based on both current development of work and years of field experience. Efforts are made to ensure that the information is reliable, however, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of continuing research and development (R&D) undertaken in our laboratories, we advise customers to ensure that the data sheets provided are not superseded by an updated publication. All products are sold are subject to our standard condition of sale, which is available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local SOLID representative.



Trusted & Certified



Find us on
Social Media



solidgreentech



FACTORY OFFICE

Lot 772 (10-14), Jalan Subang 4, Kawasan Perindustrian Sg. Penaga
47620 Subang Jaya, Selangor Darul Ehsan, MALAYSIA.

+603-8081 4777 / 4776

+603-8081 4771

info@solidolutions.com.my www.solidolutions.com.my