



# SOLIDFIX PASTE

Ready Mixed, Acrylic Polymer Based Crack Filler



## BENEFITS

- > Ready to use.
- > Excellent consistency for gap filling. It's dense and cohesive properties will protect from seepages.
- > Excellent adhesion.
- > Can be used on all common type of building interiors and exteriors.
- > High performance non structural crack filling paste.
- > Ensures surface breathability.
- > Fantastic chemical resistance.
- > Non toxic and safe to use.

## DESCRIPTION

**SOLIDFIX PASTE** is a ready mixed, easy to use, acrylic polymer based crack filling paste, which ensures perfect filling of cracks and will not allow water penetration.

## USES

- > Designed for filling cracks and holes in and around plaster, wood, bricks, stones, concrete, stucco, primed metal, fibre cement and other masonry surfaces.
- > It is specifically formulated to fill cracks that might be unstable due to normal expansion and contraction as a result of temperature changes, but it is not recommended for structural repairs.
- > Ideal for filling cracks where adhesion problems occur.
- > Areas of use include the repair of glazing where old putty has cracked or chipped off.

## TYPICAL PROPERTIES

Appearance	Smooth Paste
Color	White
Solid Content	80%
Viscosity	Paste
Flash Point	Non Flammable
Drying Time : Touch Dry	1 Hour @ 25 °C
Re-coating Interval	2 Hours @ 25 °C



## PACKING & COVERAGE

**SOLIDFIX PASTE** is available in 5 & 20 kg bucket. 1 kg of **SOLIDFIX PASTE** will approximately cover cracks having the width and depth of 15 ~ 10mm.

## SHELF LIFE & STORAGE

**SOLIDFIX PASTE** will have a shelf life of 12 months in unopened container when kept in dry conditions at a temperature between 5 ~ 45 °C. Storage at higher temperature or high humidity may reduce shelf life. The product is best stored away from direct sun, heat and severe cold. Also, protect from freezing.

## HEALTH & SAFETY

If skin or eye contact occurs, wash thoroughly with clean water and seek medical advice. Full health and safety details are given in product safety data sheet.

# SOLIDFIX PASTE



## HOW TO USE

**Surface Preparation :** Ensure all surfaces are thoroughly cleaned and allowed to dry.

**Application :**

- > Best results are obtained when the product is mixed before use and knifed smooth using a wet putty knife.
- > Apply with a putty knife in layers from 1~10mm thick. Thicker fills should be done in two or more stages.
- > **SOLIDFIX PASTE** best be sanded using a mild sand paper to achieve a smoother surface for further finishes.
- > Although the surface may be left unpainted, it should not be exposed to permanently wet conditions. Therefore, it is advantageous to overcoat **SOLIDFIX PASTE** with either an appropriate emulsion or enamel paint system. Refer to **SOLIDCOAT / SOLIDSHIELD / SOLIDLITE** data sheets for more information on paint.

## QUALITY ASSURANCE

**SOLID** manufactures the entire range of construction chemical under compliance of SIRIM and other international standards (ASTM, BS, GBI, LEED).

## TECHNICAL SERVICES

While new advance and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel and experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

**Disclaimer :** The information provided in the data sheets is based on both current development of work and years of field experience. Efforts are made to ensure that the information is reliable, however, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of continuing research and development (R&D) undertaken in our laboratories, we advise customers to ensure that the data sheets provided are not superseded by an updated publication. All products are sold are subject to our standard condition of sale, which is available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local **SOLID** representative.



### FACTORY OFFICE

Lot 772 (10-14), Jalan Subang 4, Kawasan Perindustrian Sg. Penaga  
47620 Subang Jaya, Selangor Darul Ehsan, MALAYSIA.

+603-8081 4777 / 4776

+603-8081 4771

info@solidolutions.com.my www.solidolutions.com.my